



HIGH FREQUENCY HORNS AND HORN/LENS ASSEMBLIES

BOCINAS Y LENTES ACÚSTICAS



TD 250



TD 235



TD 580



TD 400

SPECIFICATIONS

MODEL	TD/800	TD/580	TD/235	TD/300 LA-85	TD/140 LA-55	TD/400	TD/250
Type	Expon.	Radial	Constat Directivity	Slant Plate	Folded Plate	Constant Directivity	Constant Directivity
Directivity HxV	100°x40°	90°x40°	90°x40°	140°x45°	100°x40°	90°x40°	90°x40°
Crossover Frequency	300 Hz	600 Hz	800 Hz	500 Hz	800 Hz	450 Hz	600 Hz
Throat Ø	2" 49 mm.	1" 25 mm.	1" 25 mm.	2" 49 mm.	1" 25 mm.	2" 49 mm.	1" 25 mm.
Dimensions height x width x depth	270x820 x530 mm.	170x570 x379 mm.	172x235 x92 mm.	310x850 x525 mm.	170x500 x340 mm.	270x420 x227 mm.	195x420 x170 mm.
Cut Out Dimensions Height x width	220x720 mm.	140x510 mm.	135x190 mm.	160x300 mm.	108 mm.	230x365 mm.	165x380 mm.